

NEW COVE WHEEL

Introducing the **NEW BORIDE Cove Wheel**! Say goodbye to heavy, metal bond radius wheels. The BORIDE Cove Wheel is made of lightweight aluminum, which reduces ergonomic strain and minimizes wear on your machines. The segments feature a transitional hybrid bond that offers sufficient aggressiveness to remove material, while also being easier to use for refining scratches with resins.

Transitional hybrid bond segments



Grit	Cove Wheel (3/4" Radius)
	6"
30	6996030B
50	6996050B
100	6996100B
200	6996200B

TERRAZZO EDGING

BORIDE's complete edging system enhances the quality of edge work and eliminates the need for a metal bond cup wheel. The Easy Edge™ is a rigid cup wheel and our most aggressive option. The Edge Flex™ and EdgeXcel are less aggressive alternatives to the Easy Edge™. Their flexibility is ideal for uneven areas and more forgiving for new operators. Our corner tool is designed for a multi-tool to reach tough areas. All our edging tools can be used wet or dry.

CORNER TOOL




- Polish deep into corners and hard-to-reach areas
- Corners, edges, stairs, and door jambs
- Available in 30, 50, 100, 200 and 400 grit
- Recommend using wet for OSHA compliance
- Starter pack of each grit available (Item #696000B)

EASY EDGE™




- Use with hand grinders or walk-behind grinders
- Threads/Adapter: 5/8"- 11", Metric M14 and Hilti DGH 150
- Available in 4", 5", 6" and 7"
- Expected lifespan: 10-16 hours

EDGE FLEX™



- Grind non-flat surfaces like curbs and drains
- Expected lifespan: 6-8 hours
- Full Velcro backing (flexible foam adaptor available)
- More forgiving for new operators

EDGEXCEL



- More aggressive for removal of mastic, paint or glue
- Grind non-flat surfaces like curbs and drains
- Expected lifespan: 6-8 hours
- Velcro attachment requires adaptor available at BORIDE
- More forgiving for new operators

	Corner Tool	Easy Edge™ (5/8"-11" Thread)		Edge Flex™		EdgeXcel Flex Pad	
Grit	2 Pack	7"	5"	7"	5"	7"	5"
30	696030B2	695352B	695368B	695498B	695493B	695910B	695900B
50	696050B2	695361B	695369B	695499B	695494B	695911B	695901B
100	696100B2	695353B	695370B	695500B	695495B	695912B	695902B
200	696200B2	695354B	695371B	695501B	695496B	695913B	695903B
400	696400B2	695362B	695372B	695502B	695497B	695914B	695904B
800	-	-	-	6955322B	695530B	695915B	695905B
1500	-	-	-	695523B	695521B	695916B	695906B

TERRAZZO FLOOR

BORIDE's transitional bonded floor diamonds are designed for honing processes following the metal bond process. These diamonds result in superior floors and a more efficient process. Our resins are specifically tailored to complement our transitional line. We offer both dry polishing and wet polishing resins. Our BSD resin line enables contractors to complete their terrazzo polishing process with the same quality, long life, and dependability for which BORIDE products are known.

BSD




- Designed to follow the First Cut 4 Segment
- Long life (10,000-15,000 ft²)
- Velcro or speedshift dovetail attachment
- Small, medium, & large planetary machines
- Available in soft, standard, or hard bonds

PREMIUM 8 SEG TRANSITIONAL




- Reduces metal bond steps
- Long life (15,000-25,000 ft²)
- Velcro or speedshift dovetail attachment
- Small, medium, & large planetary machines
- Available in soft, standard, or hard bonds

WET RESINS



- Used for wet grinding applications
- Long life (6,000-8,000 ft²)
- Velcro or speedshift dovetail attachment
- Designed to follow transitional steps

DRY RESINS









- Used for dry grinding applications
- Long life (6,000-8,000 ft²)
- Velcro or speedshift dovetail attachment
- Designed to follow transitional steps

Grit	BSD	Premium 8 Seg	Premium 8 Seg Speedshift	BSD Speedshift	Wet Resin	Dry Resin
30	7134	7155	7181B	71304	-	-
50	7130	7156	7182	71300	-	-
80	7135	-	-	71305	-	-
100	7127	7157	7183	71207	-	-
200	7137	7241	7184	71307	-	-
400	7131	7158	7185B	71301	8635	7371
800	7132	-	-	-	8636	7372
1500	7149	-	-	-	8637	7373
3000	-	-	-	-	8638	7374

TERRAZZO PROCESS STEPS

Terrazzo

BORIDE's transitional bonded floor diamonds are designed for honing processes following the metal bond process. These diamonds result in superior floors and a more efficient process. Our resins are specifically tailored to complement our transitional line. We offer both dry polishing and wet polishing resins. Our BSD resin line enables contractors to complete their terrazzo polishing process with the same quality, long life, and dependability for which BORIDE products are known.

	TOOL	GRIT	DESCRIPTION	IMAGE
1	First Cut Premium 4 Seg or Preferred Metal Bond Tool	30/40 or 60/80	Surface Prep	
2	BSD Transitional or Premium 8 Seg	50	Expose and Hone the Floor	
3	BSD Transitional or Premium 8 Seg	100	Refined Honing	
4	BSD Transitional or Premium 8 Seg	200	Exposed/Flat Finish	
5	BSD Wet or Dry Resins	200- 1500	Polish to Desired Finish	
6	Easy Edge™, Edge Flex™, and EdgeXcel	50 100 200	Edge Honing and Polishing	
7	Cove Wheel	30- 200	Cove Honing and Polishing	