



## Assembled in Michigan

Stocked for your convenience, the TC Pad features abrasive resin segments bonded to a flexible backer, mounted on a non-woven nylon pad. With no color transfer to the floor, the pad is designed to work at maximum speed under heavy grinders for high density overlayment, conventional concrete, or terrazzo. Breathe life back into floors by using the TC Pad to restore a previously polished surface. Best results when used in grit sequence; three pads at a time starting from 80 grit and ending when the desired gloss is achieved.

## TC Pad



Item #	Size	Description	Grit
685121	9"	TC Pad	50
685122	9"	TC Pad	80
685123	9"	TC Pad	100
685124	9"	TC Pad	200
685125	9"	TC Pad	400
685126	9"	TC Pad	800
685127	9"	TC Pad	1500
685128	9"	TC Pad	3000
685131	10"	TC Pad	50
685132	10"	TC Pad	80
685133	10"	TC Pad	100
685134	10"	TC Pad	200
685135	10"	TC Pad	400
685136	10"	TC Pad	800
685137	10"	TC Pad	1500
685138	10"	TC Pad	3000
685141	11"	TC Pad	50
685142	11"	TC Pad	80
685143	11"	TC Pad	100
685144	11"	TC Pad	200
685145	11"	TC Pad	400
685146	11"	TC Pad	800
685147	11"	TC Pad	1500
685148	11"	TC Pad	3000



### PRODUCT FEATURES

- **9", 10", and 11" sizing options**
- **Available in 50, 80, 100, 200, 400, 800, 1500, and 3000 grits**
- **10,000 sq. ft. life expectancy**
- **Coarse grits yield a lower life than finer grits**
- **Designed for dry grinding**
- **Abrasive resin segments bonded to a flexible backer then mounted to a non-woven nylon pad**
- **Single passes are normally all that is required**
- **Produces a high polish with high clarity in record time**

[BSDdiamond.com](http://BSDdiamond.com)  
[BSDsales@BorideAbrasives.com](mailto:BSDsales@BorideAbrasives.com)


PHONE 231.929.2121  
TOLL FREE 800.662.0336  
FAX 231.943.2852



**BORIDE**  
Engineered Abrasives

2615 Aero Park Drive | Traverse City, MI 49686

# GRIND • HONE • POLISH • FINISH

		30	50	80	100	200	270	400	800	1500	3000	Concrete Hardness
	EASY EDGE	4"	◆	◆		◆		◆	◆			Soft Medium Hard Very Hard
		5"	◆	◆		◆		◆	◆			
		6"	◆	◆		◆		◆	◆			
		7"	◆	◆		◆		◆	◆			
	EDGE FLEX	5"	◆	◆		◆		◆	◆	◆	◆	Soft Medium Hard Very Hard
		7"	◆	◆		◆		◆	◆	◆	◆	
	BSD CORNER TOOL	Triangle	◆	◆		◆	◆	◆				
	PREMIUM TRANSITIONAL	3" NO Boss	◆	◆		◆	◆	◆				Soft Medium Hard
		3" WITH Boss	◆	◆		◆	◆	◆				
		2" NO Boss	◆	◆		◆	◆	◆	◆	◆	◆	
		2" WITH Boss	◆	◆		◆	◆	◆	◆	◆	◆	
	4 SEG FIRST CUT	3" NO Boss	30/40	60/80		120/140						Hard
		3" WITH Boss	30/40	60/80		120/140						
	BSD	3" NO Boss	◆	◆	◆	◆	◆	◆	◆	◆	◆	Soft Medium
		3" WITH Boss	◆	◆	◆	◆	◆	◆	◆	◆	◆	
	Resins	3" (Dry and Wet)							◆	◆	◆	Soft Medium Hard Very Hard
		2" (Dry Only)							◆	◆	◆	
	BSD Power Trowel PAD	11"	◆	◆	◆	◆	◆	◆	◆	◆	◆	Soft Medium Hard Very Hard
		14"	◆	◆	◆	◆	◆	◆	◆	◆	◆	
	PREMIUM 8 SEGMENT	3" NO Boss	◆	◆		◆	◆					Very Hard
		3" WITH Boss	◆	◆		◆	◆					
	4 SEG FIRST CUT	3" NO Boss	30/40	60/80		120/140						
		3" WITH Boss	30/40	60/80		120/140						
	BSD	3" NO Boss	◆	◆	◆	◆	◆	◆	◆			
		3" WITH Boss	◆	◆	◆	◆	◆	◆	◆			

S

Soft  
Concrete  
2-3 MOHS  
< 3000 PSI

M

Medium  
Concrete  
3-5 MOHS  
3000-4000 PSI

H

Hard  
Concrete  
5-7 MOHS  
4500-6000 PSI

VH

Very Hard  
Concrete  
7-9 MOHS  
>6000 PSI