

DRY FLEX PADS

The BSD Dry Flex Pad is designed for polishing concrete and overlayment. It offers the convenience of using one pad per head, instead of 3 resin pucks. It's also great for daily maintenance, as it can remove light scratches and restore the original gloss of polished floors. It is recommended to be used with a Velcro adaptor plate.

Features

- Expected lifespan 3,000-4,000 ft²
- Available in 9" and 10" diameter
- Available in 200, 400, 800, 1500 and 3000 grit
- Superior performance on soft to very hard concrete
- Velcro Attachment
- Dry grinding only
- Packaged in quantities of 3 or 4 pads per grit



Item #	Description	Size	Grit	Bond	Concrete Hardness
699000B	Dry Flex Pads	9"	200	Standard	Soft to Hard
699001B	Dry Flex Pads	9"	400	Standard	Soft to Hard
699002B	Dry Flex Pads	9"	800	Standard	Soft to Hard
699003B	Dry Flex Pads	9"	1500	Standard	Soft to Hard
699004B	Dry Flex Pads	9"	3000	Standard	Soft to Hard
699100B	Dry Flex Pads	10"	200	Standard	Soft to Hard
699101B	Dry Flex Pads	10"	400	Standard	Soft to Hard
699102B	Dry Flex Pads	10"	800	Standard	Soft to Hard
699103B	Dry Flex Pads	10"	1500	Standard	Soft to Hard
699104B	Dry Flex Pads	10"	3000	Standard	Soft to Hard