



BSD Dry Flex Pad

Blue Star Diamond Technology

The BSD Dry Flex Pad has been developed for polishing concrete with the convenience of one pad per head, versus 3 resin pucks. It is also a great option for daily maintenance to remove light scratches and restore the original gloss of polished floors. Recommended for use with a velcro adaptor plate.



American Concrete Institute

Always advancing



PRODUCT FEATURES

- Superior performance on soft to very hard concrete
- Available in 200, 400, 800, 1500 and 3000 grit
- Velcro Attachment; Velcro adaptors available for purchase
- Available in 9" and 10" diameter
- Dry grinding only
- Expected life 3,000 - 4,000 sq. ft.
- Packaged in quantities of 3 or 4 per grit

BSD Item #	Size	Description	Grit	Product Hardness	Concrete Hardness
699000	9"	Dry Flex Pads	200	Standard	Soft to Hard
699001	9"	Dry Flex Pads	400	Standard	Soft to Hard
699002	9"	Dry Flex Pads	800	Standard	Soft to Hard
699003	9"	Dry Flex Pads	1500	Standard	Soft to Hard
699004	9"	Dry Flex Pads	3000	Standard	Soft to Hard
699100	10"	Dry Flex Pads	200	Standard	Soft to Hard
699101	10"	Dry Flex Pads	400	Standard	Soft to Hard
699102	10"	Dry Flex Pads	800	Standard	Soft to Hard
699103	10"	Dry Flex Pads	1500	Standard	Soft to Hard
699104	10"	Dry Flex Pads	3000	Standard	Soft to Hard



BSDdiamond.com
BSDsales@BorideAbrasives.com

PHONE 231.929.2121
 TOLL FREE 800.662.0336
 FAX 231.943.2852




Made in the USA

BORIDE
 Engineered Abrasives

2615 Aero Park Drive | Traverse City, MI 49686

GRIND • HONE • POLISH • FINISH



			30	50	80	100	200	270	400	800	1500	3000	Concrete Hardness	
EASY EDGE	4"		◆	◆		◆		◆	◆				Soft Medium Hard Very Hard	
	5"		◆	◆		◆		◆	◆					
	6"		◆	◆		◆		◆	◆					
	7"		◆	◆		◆		◆	◆					
EDGE FLEX	5"		◆	◆		◆		◆	◆	◆	◆			
	7"		◆	◆		◆		◆	◆	◆	◆			
BSD CORNER TOOL	Triangle		◆		◆	◆		◆						
STANDARD Bond	PREMIUM TRANSITIONAL	3" NO Boss	◆	◆		◆	◆		◆					Soft Medium Hard
		3" WITH Boss	◆	◆		◆	◆		◆					
		2" NO Boss	◆	◆		◆	◆	◆	◆	◆				
		2" WITH Boss	◆	◆		◆	◆	◆	◆	◆	◆			
4 SEG FIRST CUT	3" NO Boss		30/40	60/80	120/140								Hard	
	3" WITH Boss		30/40	60/80	120/140									
BSD	3" NO Boss	◆	◆	◆	◆	◆		◆	◆	◆			Soft Medium	
	3" WITH Boss	◆	◆	◆	◆	◆		◆						
Resins	3" (Dry and Wet)							◆	◆	◆	◆		Soft Medium Hard Very Hard	
	2" (Dry Only)							◆	◆	◆	◆			
BSD Power Trowel PAD	11"		◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	Soft Medium Hard Very Hard	
	14"		◆	◆	◆	◆	◆	◆	◆	◆	◆	◆		
SOFT Bond	PREMIUM 8 SEGMENT	3" NO Boss	◆	◆		◆	◆						Very Hard	
		3" WITH Boss	◆	◆		◆	◆							
	4 SEG FIRST CUT	3" NO Boss		30/40	60/80	120/140								
		3" WITH Boss		30/40	60/80	120/140								
	BSD	3" NO Boss	◆	◆	◆	◆	◆		◆					Hard
		3" WITH Boss	◆	◆	◆	◆	◆		◆					

S

Soft
Concrete
2-3 MOHS
< 3000 PSI

M

Medium
Concrete
3-5 MOHS
3000-4000 PSI

H

Hard
Concrete
5-7 MOHS
4500-6000 PSI

VH

Very Hard
Concrete
7-9 MOHS
>6000 PSI